

# PERFECT PROOF CPF - 901

CHEMPROOF

욕실 베란다 침투 방수제

Waterproofing System

BATHROOM & VERANDA - WATERPROOFING

## ● 특징

CPF - 901은 액상의 모세관 침투 결정반응성을 가진 침투성방수제로 콘크리트의 방수 및 물성계량을 목적으로 사용합니다. 무독성 폴리머와 규산질계의 공중합 반응으로 콘크리트의 미세공극에 침투하여 규산칼슘과 반응하는 특성을 가지고 있습니다. 또한 방수성, 내마모성, 수밀성, 강도를 향상시킵니다.

## ● 용도

- 욕실, 타일메지 시공 시 베란다, 보일러 실, 타일 바닥, 콘크리트, 크랙부위, 옥상바닥 외 침투가 가능한 모든 부위, 보호 몰탈, 견출방수.

## ● 주의사항

- 5°C 이하에서는 사용을 금하고, 제품 보관 시 동결에 주의 하십시오.
- 실내에 보관하십시오.
- 원액으로 사용하며 사용 후 잔량은 밀폐하여 보관하고 어린이 손에 닿지 않도록 보관합니다.
- 피부에 묻었을 경우 2시간 이내에 흐르는 물에 세척합니다.

## ● 사용방법

타일, 벽돌메지 시공 시 백시멘트나 메지몰탈에 첨가하여 사용하면 방수 및 강도의 효과가 더욱 우수합니다.

1. 시공 부위의 기름, 이끼, 유분, 오물찌꺼기 등을 깨끗이 청소합니다.
  - 청소 시 산성분이 있는 세척제는 사용하지 않도록 합니다.
  - 시공부위에 물기가 있을 경우 반드시 건조 후 시공합니다.
  - 균열이 심한 부위 (1mm) 는 시공 후 균열부위를 보수하도록 합니다.
  - 시공면의 습윤 상태는 30% 미만이어야 합니다.
2. 붓, 롤러, 방수비를 이용하여 메지 (줄눈) 부위를 중점으로 도포하여 원액이 침투되도록 합니다.
3. 초기의 시공 작업이 중요하므로 많은 양을 투입합니다.
4. 충분히 침투시킨 후 수건을 이용하여 타일 면을 닦아주도록 합니다.
5. 재 도포시 1시간 경과 후 2차 도포를 시행하고 24시간 동안 건조 시킵니다.

## ● 포장단위 / 색상

- 4Liter, 18Liter Pail / 색상 : 미백색



## ● Feature

CPF - 901 is a permeable waterproofing agent used to measure the waterproofing and physical properties of concrete. It has the property of penetrating into the micropores of concrete and reacting with calcium silicate by the copolymerization reaction of non-toxic polymer and siliceous system. It also improves waterproof, abrasion resistance, water tightness and strength.

## ● Uses

- In the bathroom, tile installation, veranda, boiler room, tile floor, concrete, crack, rooftop bottom, all parts where penetration is possible.

## ● Precautions

- Do not use below 5°C and Please be careful when freezing the product.
- Please keep it inside.
- Keep the remaining amount sealed after use.
- Keep out of reach of children.
- If it gets on your skin, wash it in running water within 2 hours.

## ● How to use

Tile and brick is added to white cement of magemortar when it is applied, have better waterproofing and strength.

1. Clean the oil, moss and dirt on the construction site thoroughly.
  - Do not use cleaning agents containing acidic substances during cleaning.
  - If there is water on the construction site, be sure to dry after construction.
  - The cracked area (1mm) will repair the cracked area after construction.
  - The wetness of the construction surface should be less than 30%.
2. Using th bursh roller and waterproof bursh, apply the focusing on the joint part so that the undiluted solution is infiltrated.
3. Use enough volume for 1st coating.
4. After thoroughly penetrating, wipe the tile surface with a towel.
5. After 1 hour of re-application, apply 2nd application and dry for 24 hours.

## ● Packing Unit & Color

- 4Liter, 18Liter Pail & Color : Yellow White



\* For further information, please refer to Material Safety Data Sheet (MSDS).  
\* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominum, No. (483) ,  
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)  
MP : 09-44476-7045 (Korean & English)



16gil - 6 Jinjang Bukgu, Ulsan, Korea  
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259  
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)



Registered ISO 9001 , 14001

# PERFECT PROOF CPF - 901

CHEMPROOF

욕실 베란다 침투 방수제

Waterproofing System

BATHROOM & VERANDA - WATERPROOFING

● Feature

CPF-901 သည် ရေချိုးခန်း ၊ ဝရံတာများတွင်သုံးသည့် waterproofing agent ဖြစ်ပါသည်။ ၎င်းတွင် ကွန်ကရစ်အတွင်းပိုင်းအထိ စိမ့်ဝင်ပျံ့နှံ့နိုင်သည့် အစွမ်းသတ္တိ ရှိပါသည်။

● Uses

ရေချိုးခန်း ကြော့ပြားကပ် ၊ ဝရံတာ ၊ ဘိုင်လာခန်း ၊ ကြော့ပြားကြမ်းခင်း ၊ ကွန်ကရစ် roof top ကြမ်းခင်း အစရှိသည့် ရေစီးကြောင်းဖြစ်နိုင်သည့် မည်သည့်နေရာတွင် မဆို အသုံးပြုနိုင်ပါသည်။

● Precautions

- 5°C အောက်အပူချိန်တွင် အသုံးမပြုရ။
- အဆောက်အဦး အတွင်း၌သာ သိမ်းဆည်းပါ။
- ခဲနေလျှင် အသုံးမပြုရ။
- အသုံးပြုပြီး ပိုနေလျှင် လေလုံအောင် ပြန်ပိတ်ထားပါ။
- ကလေးများနှင့် ဝေးရာတွင်ထားပါ။
- အရေပြားနှင့်ထိတွေ့မိလျှင် ၂ နာရီအတွင်း ရေဖြင့် ဆေးကြောပါ။

● How to use

1. လုပ်ငန်းခွင်နေရာအား ဆီများ ၊ ဖုန်မှုန့်များ ၊ အမှိုက်သရိုက်များ မရှိအောင် သေသေချာချာ သန့်ရှင်းပါ။ သန့်ရှင်းရာတွင် အက်ဆစ်ပါသော cleaning agent များကို အသုံးမပြုရ။
2. လုပ်ငန်းခွင်နေရာတွင် ရေများရှိပါက ခြောက်သွေ့အောင်ပြုလုပ်ပါ။ အကယ်၍ မျက်နှာပြင် စိုစွတ်နေလျှင် စိုစွတ်မှုသည် ၁၀% အောက် ရှိသင့်သည်။
3. Brush or Roller ကိုအသုံးပြုပြီး ကျောက်ပြား ၊ ကြော့ပြားကြားထဲသို့ ဆေးထည့်ပါ။
4. လုံလောက်သည့်ဆေးပမာဏအားထည့်ပါ။ ကျောက်ပြားများအကြား သေချာစွာ စိမ့်ဝင်သွားပြီးလျှင် ကျောက်ပြားမျက်နှာပြင်အား အပတ်ဖြင့်သုတ်ပါ။
5. ပထမတစ်ခေါက်သုတ်ပြီး ၁ နာရီအကြာတွင် ဒုတိယတစ်ခေါက် သုတ်ပါ။ ၂၄ နာရီ ကြာ အခြောက်ခံပါ။

● Packing Unit & Color

- 4Liter, 18Liter Pail & Color : Yellow White



● Feature

CPF - 901 is a permeable waterproofing agent used to measure the waterproofing and physical properties of concrete. It has the property of penetrating into the micropores of concrete and reacting with calcium silicate by the copolymerization reaction of non-toxic polymer and siliceous system. It also improves waterproof, abrasion resistance, water tightness and strength.

● Uses

- In the bathroom, tile installation, veranda, boiler room, tile floor, concrete, crack, rooftop bottom, all parts where penetration is possible.

● Precautions

- Do not use below 5°C and Please be careful when freezing the product.
- Please keep it inside.
- Keep the remaining amount sealed after use.
- Keep out of reach of children.
- If it gets on your skin, wash it in running water within 2 hours.

● How to use

Tile and brick is added to white cement of magemortar when it is applied, have better waterproofing and strength.

1. Clean the oil, moss and dirt on the construction site thoroughly.
  - Do not use cleaning agents containing acidic substances during cleaning.
  - If there is water on the construction site, be sure to dry after construction.
  - The wetness of the construction surface should be less than 30%.
2. Using th bursh roller and waterproof bursh, apply the focusing on the joint part so that the undiluted solution is infiltrated.
3. Use enough volume for 1st coating.
4. After thoroughly penetrating, wipe the tile surface with a towel.
5. After 1 hour of First coat and then apply 2nd coat and dry for 24 hours.

● Packing Unit & Color

- 4Liter, 18Liter Pail & Color : Yellow White



\* For further information, please refer to Material Safety Data Sheet (MSDS).  
\* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominum, No. (483) ,  
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)  
MP : 09-44476-7045 (Korean & English)



16gil - 6 Jinjang Bukgu, Ulsan, Korea  
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259  
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)



Registered ISO 9001 , 14001